



# DJM Monitor Boxes For Temperature Controllers



A QUALITY PRODUCT

**EXPLOSIONPROOF**

For UL.60079-1 Standard Class I, II Div. 2 Groups C,D,E,F and G

For IEC.60079-0/1 Standard Zone 2

## Technical data

Type of Protection: Ex d IIA T6

Conforming to : Standards IEC 60079-1 or UL 60079-0/1

Marking for test : Ex II2G

Degree of Protection : IP66 acc.To IEC 60529

Ambient Temp. (Ta) : -20°C to +55°C Temp.class T6

Type :DJM

Protection class for UL. : Class I, Division 1, 2 Group.C,D

Class II, Division 1 or 2 Groups.E,F,G

Class III

Protection class for IEC : Zone 1 , 2

Cable Gland : PG9 and PG6

Contact rating 220V.AC.



ISO9001:2008



DJM

## Specification

Body,Cover : Copper-free aluminium alloy with epoxy-polyester powder coated.

Seal gasket : Silicone -40°C to +175°C

Lens : Heat and impact resistant glass

## Catalogue Nubmer:

| Cat. No.     | Cable Gland          |   |        | Dimension in mm. |    |     |    |     | Approx. Weight |
|--------------|----------------------|---|--------|------------------|----|-----|----|-----|----------------|
|              | Outer Diameter (mm.) |   |        | a                | b  | c   | d  | e   |                |
|              | PG6                  | + | PG9    |                  |    |     |    |     | (kgs.)         |
| DJM - VD2003 | 4. - 7               |   | 5. - 9 | 156              | 88 | 114 | 44 | 157 | 2              |

Remark:

In case the enclosures are supplied completely with control units or devices, They will be delivered with conformity certificate and can be used without further testing. supply temperature controllers for VD-2003 series and Vertex brand.

## Catalogue Nubmer:

