

Incandescent and Compact Fluorescent Lighting Fixture, ECN-B Series

Technical data:

Explosion Protection	: Ex d IIB T4 or T6
Conforming to	: Standards IEC 60079-0/1 or UL 60079-1
Marking for test	: Ex II2G
Degree of Protection	: IP54 / 66 acc. To IEC 60529
Ambient Temp. (Ta)	: -20 °C to+ 55 °C
Rated Voltage	: 220-240V AC 50/60H
Lamp holder	: E27
Connection	: L , N and E for 1-4Squmm. Cable
Mounting	: Ceiling , Pendant and Bracket
Protection class for UL.	: Class I, Division 1or 2 Group. C,D Class II, Division 1 or 2 Groups. E,F,G Class III
Protection class for IEC	: Zone1 , 21 and Zone 2 , 22

Specification:

Body and cover	: Marine grade copper-free aluminum alloy with epoxy-polyester powder coated , RAL7032(GREY)
Glass globe	: Borosilicate glass
Basket guard	: Stainless steel
Sealing gasket	: Silicone -40 °C to+ 175 °C

Options:

Adding suffix to Cat. No.
Sheet steel Suffix - S

Catalogue Number and Dimension :

Catalogue Number		
Pendant	Ceiling	Bracket
ECN-BP	ECN-BC	ECN-BB

