

Technical data:

Explosion Protection	: Ex d IIB T6/T5
Conforming to	: Standards IEC 60079-0/1
Marking for test	: Ex II2G
Degree of Protection	: IP54 / 66 acc. To IEC 60529
Ambient Temp. (Ta)	: -20 °C to+ 55 °C
Rated Voltage	: 220-240V AC 50/60Hz
Lamp	: Compact fluorescent
Lamp holder	: E27
Entries thread	: 2 x 3/4" NPT with blind plug
Connection	: L , N and E for 1-4Squmm. cable
Protection class for UL.	: Class I, Division 1or 2 Group. C,D Class II, Division 1 or 2 Groups. E,F,G Class III
Protection class for IEC	: Zone1 , 21 and Zone 2 , 22



Type ECF

Specification:

Body and cover	: Marine grade copper-free aluminum alloy with epoxy-polyester powder coated , RAL7032(GREY)
Glass globe	: Borosilicate glass
Axles and guard	: Stainless steel
Sealant	: Cast resin

Catalogue Numbers:

Lamp Watt	Temp. Class (Surface Temp.)		Cat., No
	40 °C Ta	55 °C Ta	
12w.	T6	T5	ECF 12 C
20w.	T6	T5	ECF 20 C
24w.	T6	T5	ECF 24 C

Dimension :

