

Application:

The SSL selector switches are suitable for

- used in zone 1, zone 2 and zone 21, zone 22 in hazardous locations
- use in conjunction with magnetic starters or contactors for remote control of motors.
- indoor, outdoor and corrosive locations.
- circuit control of motors.

Technical data:

Explosion Protection : Ex d IIB T6
 Conforming to : Standards IEC 60079-1 or UL 60079-0/1
 Marking for test : Ex II2G
 Degree of Protection : IP54 / 65 (option) acc. To IEC 60529
 Ambient Temp. (Ta) : -20 °C to + 55 °C
 Protection class for UL. : Class I, Division 1 or 2 Group. C, D
 : Class II, Division 1 or 2 Groups. E, F, G
 : Class III
 Protection class for IEC : Zone 1 , 21 and Zone 2 , 22
 Conduit hub size : 3/4" NPT



Specification:

Body and cover : Marine grade copper-free aluminum alloy
 with polyester powder coated , RAL 7032 (Grey)
 Lid screws : Stainless steel

Options:

Silicone rubber on cover selector switches Type **R** for **IP66**

Rating:

Contact rating : 3A. 220V.AC.
 Rated insulation current : 10A.
 Rated insulation voltage : 600 v.

Catalogue Number:

Number of contact	Diagram Left Center Right	Nameplate Marking	Cat.,No	
			Dead-end (1 hub)	Through-feed (2 hub)
2 - Positions				
1NO		OFF - NO	SSL 210	SSL 210H
2NO		OFF - NO	SSL 220	SSL 220H
1NO - 1NC		MAN. - AUTO	SSL 211	SSL 211H
3 - Positions				
2NO		MAN. - OFF - AUTO	SSL 320	SSL 320H
2NC		Specify	SSL 302	SSL 302H

