

Application data :

The DCH flexible cushion fixture hangers are used

- for zone 1, 2 and zone 22 hazardous areas
- for suspension of H.I.D., fluorescent or incandescent lighting fixtures.
- to protect the fixture, stem and to support outlet box from damage in an accidental shock or vibration.

Technical data :

Explosion Protection	: Ex d IIB T6
Conforming to	: Standards IEC 60079-0/1 or UL 60079-1
Marking for test	: Ex II2G
Degree of Protection	: IP54 acc. To IEC 60529
Ambient Temp. (Ta)	: -20 °C to +75 °C
Protection class for UL.	: Class I, Division 1 or 2 Group. C,D Class II, Division 1 or 2 Groups. E,F,G Class III
Protection class for IEC	: Zone 1, 21 and Zone 2, 22
Conduit hub	: 1/2" - 3/4" NPT.

Specification:

Body and cover	: Marine grade copper-free aluminum alloy with epoxy-polyester powder coated , RAL7032(GREY)
----------------	---

Catalogue Numbers and Dimensions: in mm.

Conduit Size	NPT (inch)	Cat. No.
1 Hub	1/2" NPT	DCHB11
	3/4" NPT	DCHB22
2-Hubs Straight	1/2" NPT	DCHC11
	3/4" NPT	DCHC22
2 Hub Angle	1/2" NPT	DCHL11
	3/4" NPT	DCHL22
3 Hub	1/2" NPT	DCHT11
	3/4" NPT	DCHT22
4 Hub	1/2" NPT	DCHX11
	3/4" NPT	DCHX22



DCHB



DCHL



DCHC



DCHT



DCHX

