

Technical data:

Explosion Protection	: Ex d IIB T6
Conforming to	: Standards IEC 60079 - 0 to 1 or UL 60079-1
Marking for test	: Ex II2G
Degree of Protection	: IP54/65 acc. To IEC 60529
Ambient Temp. (Ta)	: - 5°C to + 55°C
Rated Voltage	: 220 - 240 V. AC. 50/60Hz.
Lamp	: 10 w. For LED
Battery	: 6V. 4Ah (Flu. and Compact Flu.)
Recharge time	: 24-hours from fully discharge
Emergency duration	: 2-hours
Entries thread	: 1/2" NPT
Protection class for UL.	: Class I, Division 1or 2 Group. C,D Class II, Division 1 or 2 Groups. E,F,G Class III
Protection class for IEC	: Zone1 , 21 and Zone 2 , 22



EXIT-R2010LA



EXIT-R2010LB

Specification:

Body material	: Marine grade copper-free aluminum alloy with epoxy-polyester powder coated , RAL7032 (GREY)
Lens	: Heat and impact resistant clear glass
Sing face	: White, Green acrylic with red, white color letters.

Catalogue Numbers:

Lamp Watts	Temp. Class (Surface Temp.)		Cat., No.
	40 °C Ta	55 °C Ta	
LED (Chip)			
10 W.	T6	T6	EXIT-R2010LA
10 W.	T6	T6	EXIT-R2010LB

Dimension :

