

Technical data:

Type of Protection	: Ex d IIB T4/T6
Conforming to	: Standards IEC 60079-0 to 1 or UL 60079-1
Marking for test	: Ex II2G
Degree of Protection	: IP54/ IP66 (Option) acc. To IEC 60529
Ambient Temp. (Ta)	: -20°C to + 40°C or + 55°C
Rated Voltage	: 220 - 240 V. A.C 50Hz.
Lamp (LED)	: 9 W. or 12 W.
Color Temperature	: Daylight (6000K ± 250K)
Luminous Intensity	: 726 lm, Daylight (9W) ,910 lm, Daylight (12W)
Testing System	: Auto Check
Battery Type	: Lithium Iron Phosphate (LiFePO4) 3.2V-6000mAh x2
Charging Period	: 10-15 hours
Back up time	: 3 hours
Protection Features	: AC,DC Fuse ,Battery Low Voltage Cut-Off
Entries thread	: 3/4" NPT at right
Protection class for UL.	: Class I, Division1 or 2 Group. C,D Class II, Division1 or 2 Groups. E,F,G Class III



TYPE D

Specification:

Body and cover	: Marine grade copper-free aluminum alloy with epoxy-polyester powder coated , RAL7032 (GREY)
Sealing gasket	: Silicone -40°C to + 175°C
Lid screws	: Stainless steel

Catalogue Number:

Lamp Watts	Cat., No	Temp. Class	
		Ta 40 ° C	Ta 55 ° C
LED Lamp			
2 x 9w.	EMG209	T6	T6
2 x12w.	EMG212		

Dimension:

TYPE D (Push Button—TEST Only)

